

- Size:** 500 x 500 mm with +/- 0.5 mm tolerance sideways per 500 mm and +/- 0.7 mm diagonal
- Weight:** **275 grams** (=+ 275 gr =/- 280 gr)
- Thickness:** **based on weight of 275 grams**
Approx 1.75 mm (1 model = 1 batch = +/- tolerance of 0.05 mm)
- Height:** thickness of panel + 15 mm (Total approx 16.75mm)
- Surface:** smooth without cracks
- Cutting edge:** 90 degrees with +/- 0.5 mm tolerance sideways per 500 mm and +/- 0.7 mm diagonal
- Material:** white bagasse (natural bleached sugarcane pulp)
- Treatment:** natural water and oil resistance agents added
- Retail pack:** 12 panels covers 3m² or 32 square feet
- Description:** Pulp of Sugarcane Bagasse or of other Fibrous Cellulosic Material; Moulded or pressed articles of Sugarcane Bagasse pulp or of other Fibrous Cellulosic Material. Other pulp, cellulose wadding and webs of cellulose fibres, cut to size or shape; other articles of Sugarcane Bagasse pulp, cellulose wadding or webs of cellulose fibres.
- flammability class:** Class C, but we advice to use Class A fire proof coating / fire retardant paint like DC333 after installing for best and safest result!

